



Providing Solutions.

Phone: 916-638-7718 Fax: 916-638-2450

www.scottmachinery.com

4700 Lang Ave, Suite D, Mcclellan, CA 95652

# Lathes – PL-1236E-DRO



SPECIFICATIONS – PL-1236E-DRO		
Swing Over Bed	12"	305 mm
Swing Over Cross Slide	7.625"	194 mm
Swing in Gap	17"	431 mm
Distance Between Centers	36"	914 mm
Length of Gap	6"	152 mm
Width of Bed	7.125"	181 mm
Spindle Nose	D1-4"	
Spindle Bore	1.50"	38 mm
Spindle Bore Taper	Morse #5	
Spindle Speeds	9 (70 – 1400 rpm)	
Travel of Top Slide	3.250"	83 mm
Travel of Cross Slide	5.312"	135 mm
Max. Tool Selection	.625" x .625"	16 mm x 16 mm
Leadscrew Thread Pitch	8 T.P.I.	
Longitudinal Feed Range	0.002" – 0.0548"/rev	.05 – 1.4 mm/rev
Cross Feed Range	0.007" – 0.0187"/rev	.178 – .475 mm/rev
Metric Thread Range	0.4 – 7 mm	
Sleeve Diameter	1.250"	32 mm
Sleeve Travel	4"	101 mm
Sleeve Taper	Morse #3	
Power Requirements	110V, 1-phase	
Horsepower	1.5	
Shipping Dimensions (L x W x H)	67" x 31" x 60"	1701 x 787 x 1524 mm
Shipping Weight	1,232 lbs.	560 kgs.

Specifications subject to change without notice.

- ◆ 2-axis digital readout
- ◆ 6" three jaw chuck
- ◆ 8" four jaw chuck
- ◆ Face plate
- ◆ Steady rest
- ◆ Follow rest
- ◆ Live center
- ◆ Quick change tool holder
- ◆ Foot brake
- ◆ Coolant system with splash guard
- ◆ Removable chip tray
- ◆ 110V/220V dual voltage

