


H 400 A H 400 A-NC

Fully automatic, fully hydraulic heavy one piece unified construction for superb alignment and accuracy.

- Fully hydraulic
- Manual mitering up to 60 degrees
- Feeder stroke 20" w/ unlimited indexes
- Scrap end 5"
- Carbide guides w/ rollers
- Time saving material sensor
- Easy setup
- Top clamp
- Feeder accuracy +/- 0.008" per index

H400 A-NC additional features

- Job memory
- Ball screw feeder +/- 0.005" per index



Ball screw on H 400 A-NC



04.

Accessories on pages 38-43



Providing Solutions

Tollfree Ph 888-906-4350
Email: sales@scottmachinery.com

www.scottmachinery.com

5209 Luce Avenue, Bldg. 243-B, McClellan, CA 95652



Standard Equipment

- One HSS bi-metal sawblade
- Low-volt control Low-volt/undervolt shutoff
- Blade tension indicator
- Broken blade shutoff
- Infeed/Outfeed support rollers
- TEFC 3 phase drive motor
- Totally enclosed worm gear transmission
- Blade brush
- Full Coolant System
- Full Blade Guarding
- Operators Manual Parts List/Schematics
- Tool kit

H 400 A & H 400 A-NC Specifications				OPTIONAL	
0°	12"	10 1/4"	7 3/4 x 13 1/2"	230/3	opening
45°	10"	9"	7 3/4 x 9"	460/3	15"
60°	6 3/4"	6"	4" x 6 1/2"		
3HP	60-360	H 1.25"	2100 lbs	W 86"	L 70"
					Workheight 37"
		13' 2"			

Capacities shown are max envelope. Each individual cutting job must be considered with regards to type and shape of material, and quantity of pieces per day.