




MODEL GBAC ROTO BINDER

A roll coating application system featuring high production rates, minimal maintenance, and operator safety

Duro Dyne was the first company to introduce an adhesive designed strictly for fastening insulation to steel. Since that time Duro Dyne has continued to incorporate the latest technological advances in its adhesive line. As the need for a low cost non-flammable adhesive grew, Duro Dyne pioneered the introduction of a quality water based adhesive which is both economical and

safe to apply. The technological development makes possible low cost, high production roller application of adhesive. To realize the fullest production potential of water based adhesive, Duro Dyne designed the Roto Binder; a production machine which rapidly applies adhesive to insulation prior to bonding to metal.



Fast

The GBAC is capable of coating fiberglass duct liner at the rate of 52' per minute. Using a standard roll of material - 5' wide, the GBAC coats over 250 square feet of liner per minute.

Versatile

GBAC's are quickly adjusted to accept liner ranging for 1/2 to 2 inch thickness.

Reliable

Using the highest quality components, the Roto Binder is built to withstand the rigors of high production shop usage.

Easy to Use

The Roto Binder pumps adhesive from a drum into a built-in storage tank. A circulating system maintains proper adhesive level. Simply turn on the power and feed the liner material into the GBAC. There is no over spray or dangerous solvent fumes.

Fast Cleanup

The GBAC cleans with plain water in minutes. All parts are easily accessible to the operator.

High Production

The GBAC works with existing Insulation Sizing machines and can be used in conjunction with an Automatic Pinstotter for a low cost high efficiency production line.

Service

Duro Dyne distributors and sales engineers are available throughout the country to provide continuing service.



DURO DYNE EAST
Route 110
Farmingdale, NY 11735
631-249-9000
FAX: 631-249-8346

DURO DYNE MIDWEST
3825 Symmes Rd.
Fairfield, OH 45011
513-870-6000
FAX: 513-870-6005

DURO DYNE WEST
15005 Marquardt Ave.
Santa Fe Springs, CA 90670
562-926-1774
FAX: 562-926-5778

DURO DYNE CANADA
5030 Francois-Cusson
Lachine, Quebec, Canada H8T 1B3
514-422-9760
FAX: 514-636-0328

Roto Bonder

The Roto Bonder is a machine designed specifically for the purpose of roller coating one side of duct liner with adhesive prior to joining to the metal section of the duct. Insulation up to 60" wide can be evenly coated at a rate of 52' per minute. Either Duro Dyne's WSA or WIT adhesive can be used. Both are water base non-flammable adhesive and are available in 55 gallon drums or 5 gallon pails.

The Roto Bonder contains a trough through which the lower of two rollers rotates. The lower roller picks up adhesive, the thickness of which is controlled accurately by an adjustable metering bar. The Roto Bonder accepts insulation thickness of 1/2 to 2 inches.

Operation


Turn the multi port valve so that adhesive flows from the 60 gallon storage tank into the trough. Re-set the valve to circulate the adhesive from the tank to the trough and feed pre-cut liner material into the machine. In seconds, adhesive coated fiberglass exits automatically across the exit fingers.

At the end of the work day, pump adhesive from the trough to the storage tank. To clean the rolls, metering bar and exit rack, sponge them with water. Cover the adhesive remaining in the tank with a thin film of water and replace the tank cover.


By eliminating spraying, there is no longer any hazard of fire and dangerous fumes. No venting of fumes is necessary. Clean-up is fast and easy.

When the Roto Bonder is used in conjunction with a Liner Sizing machine and Pinspotter, it is possible for one man to perform the entire operation of adhering and pinning liner to duct sections.

Features




A heavy duty low maintenance air operated pump.




A metering bar accurately controls adhesive application.




Easy access multi-port ball valves control adhesive flow.




Safety guards are designed for maximum safety and practical shop use.



The cleanup position leaves sufficient space between the upper roll and the adhesive roll to allow for easy cleanup without endangering the operator.



A stainless steel trough provides dependable rustproof service.



A 60 gallon covered storage tank is built into the Roto Bonder.

Specifications

GBAC Code No. 39171 left to right flow

GBAC Code No. 39250 right to left flow

Motor - 1/3 horsepower motor.

Pump - air operated diaphragm type

Insulation Thickness - machine adjustable to coat insulation from 1/2" to 2" thick

Liner Width - from 12" to 60" wide

Liner Length - from 12"

Speed of Application - approximately 52' per minute

Adhesive - Duro Dyne WIT or WSA

IMPORTANT: Flow direction is determined with operator standing at control side of machine.