

# Shear, Brake, & Roll – SBR-5220 / SBR-5216

SPECIFICATIONS – SBR-5220		
Bed Width	52"	1,321 mm
Shear Capacity	20 ga. (.036")	1 mm
Bending Capacity	20 ga. (.036")	1 mm
Rolling Capacity	20 ga. (.036")	1 mm
Maximum Bend Angle	90°	
Minimum Rolling Dia.	1.70"	43 mm
Power Requirement	Manual	
Shipping Dimensions (L x W x H)	67" x 23" x 30"	1,702 x 584 x 762 mm
Shipping Weight	830 lbs.	376 kgs.

Specifications subject to change without notice.

- ◆ Combination shear, sheet metal brake, and slip roll
- ◆ 52" forming width
- ◆ 20-gauge mild steel capacity
- ◆ Manually operated
- ◆ Segmented fingers on brake
- ◆ 3-wire grooves
- ◆ Bench mounted

- ◆ Combination shear, sheet metal brake, and slip roll
- ◆ 52" forming width
- ◆ 16-gauge mild steel capacity
- ◆ Manually operated
- ◆ Segmented fingers on brake
- ◆ 3-wire grooves
- ◆ Bench mounted

SPECIFICATIONS – SBR-5216		
Bed Width	52"	1,321 mm
Shear Capacity	16 ga. (.060")	1.5 mm
Bending Capacity	16 ga. (.060")	1.5 mm
Rolling Capacity	16 ga. (.060")	1.5 mm
Maximum Bend Angle	90°	
Minimum Rolling Dia.	1.70"	43 mm
Power Requirement	Manual	
Shipping Dimensions (L x W x H)	67" x 30" x 46"	1,702 x 762 x 1,168 mm
Shipping Weight	1,200 lbs.	544 kgs.

Specifications subject to change without notice.



SBR-5220



SBR-5216



# SCOTT

M A C H I N E R Y

Ph. (916) 638-7718

Fx. (916) 638-2450

Email: [sales@scottmachinery.com](mailto:sales@scottmachinery.com)

4700 Lang Avenue, Suite D  
McClellan, CA 95652