



## V-8 ROLLFORMER

### Tooling:

#### INBOARD:

- 22-28 ga. Reinforced flat "S" slip
- 20-28 ga. Drive Cleat

#### OUTBOARD:

- 20 ga. 5/16" pocket Pittsburgh lock
- 18 ga. 7/16" pocket Pittsburgh lock
- 16 ga. 7/16" pocket Pittsburgh lock (45 feet per minute)
- 20-28 ga. Male and Female button punch snaplock
- 22-28 ga. Combination three-in-one (5/8" tap-in-lock, standing seam and right angle)
- 16-20 ga. Double seam (acme)
- 20-28 ga. Double seam (acme)
- 16-22 ga. Right angle flange
- 20-28 ga. Right angle flange

### Features:

- Quietest machine in the industry
- Eight forming stations for all roll sets
- 5 HP motor coupled to an industrial oil bath gear reducer for quiet longevity
- Heavy duty roller chain drive (no belts)
- Heavy duty 1 inch diameter stress proof roller shafts
- Large heavy duty bearings with inner races to protect roll shafts and extend the life of the machine
- 90-100 feet per minute pitch speed
- Single phase or three phase electrics
- No opening rolls on any roll set
- Heavy duty motor starter with thermal protection overloads

## VICON MACHINERY LLC

### *Manufacturing and Support*

1180 Mason Circle N • Pevely, MO 63070

Tel: 636-349-8999 • Fax: 636-326-2097



# SCOTT

MACHINERY

Ph. (916) 638-7718

Fx. (916) 638-2450

Email: [sales@scottmachinery.com](mailto:sales@scottmachinery.com)

4700 Lang Avenue, Suite D  
McClellan, CA 95652