



**Kalamazoo
Machine Tool**

Semi-automatic horizontal bandsaws allow quick and easy setup and operation. All major components are cast iron for solid, vibration-free production cutting. Machine operation is full cycle semi-automatic. Material size is automatically sensed by the sawframe. With the push of a single button, the vise clamps, sawframe makes the cut at preset rate, automatically returns to clear workpiece, vise opens, ready for the next cut. Production sawing can be very fast! Operation: Powered sawframe raise and lower, powered vise, semi-automatic operation.

Standard Equipment

- One HSS bi-metal sawblade
- Low-volt control
- Low-volt/undervolt shutoff
- TEFC 3 phase drive motor
- Totally enclosed worm gear transmission
- Full Coolant System
- Full Blade Guarding
- Operators Manual/Parts List/Schematics
- Tool kit



4700 Lang Ave, Suite D
McClellan, CA 95652
Ph 916-638-7718
sales@scottmachinery.com

**Double Mitering
45 degrees left, 60 degrees right**



**Model H310SA
10" Capacity**



**Model H350SA
12" Capacity**

SPECIFICATIONS

	H310 SA	H350SA
SIZE CAPACITY See below for details	10"	12"
BLADE DRIVE HP	2	3
BLADE SPEEDS All models infinitely variable	60-360 fpm	60-360 fpm
BLADE SIZE	1" x 9' 1"	1" x 11" 1"
MATERIAL WORKING HEIGHT From floor to table top	37"	37"
COOLANT TANK CAPACITY	5 Gal	5 Gal
VISE OPENING	12 1/2"	13 3/4"
MACHINE WEIGHT	1000 lb.	1700 lb
MACHINE FLOOR DIMENSIONS	34" X 44"	60" x 72"
AVAILABLE ELECTRICALS	3 Phase	3 Phase
CAPACITY DETAILS		
90 DEGREES	10"	12"
45 DEGREES LEFT	6"	10"
45 DEGREES RIGHT	8"	10"
60 DEGREES RIGHT	5"	6 1/2"



Automatic material sensor minimizes machine setup on semi-automatic models

Capacities shown are max round material. Each individual cutting job must be considered with regards to type and shape of material, and quantity of pieces per day.