

690055 : JTM-1055, 10" x 54" Table, #40 Taper, 5HP, 3Ph, 230/460V



Features and Benefits

- Meehanite casting
- Hardened and ground table certified to be 52C Rockwell hardness
- Chrome lead screws on X and Y axis
- Boxed style ways on Y and Z axis
- Turcite B on X and Y axis



Email: sales@scottmachinery.com

Phone# 916-638-7718

Website: www.scottmachinery.com

690055 : JTM-1055, 10" x 54" Table, #40 Taper, 5HP, 3Ph, 230/460V

Specification	Value	
Part Number	690055	
Motor	5 HP, 230/460V, 3 Ph, Prewired 230V	
Number of Spindle speeds	Variable	
Spindle Taper	NST #40	
Quill Diameter (in.)	4-1/8	
Head Movement (deg.)	90° R & L	
Max Distance Spindle to Table (in.)	20	
Distance Spindle to Column (in.)	26 (max)	
Table Longitudinal Travel (in.)	32	
Table Cross Travel (in.)	16	
Collet Capacity	1/8 - 7/8	
T-Slots Number and Size (in.)	3 and 5/8	
T-Slot Centers (in.)	2-1/2	
Work Table Weight Capacity (lbs.)	800	
Travel of Knee (in.)	17-1/2	
Travel of Ram (in.)	20-1/2	
Quill Down feed Rates (IPR)	.0015 - .003 - .006	
Range of Spindle Speeds (RPM)	80 - 3800	
Table Size (in.)	10 x 54	
Note	Use of static phase converter will void warranty	
Distance Spindle to Column (min./in.)	5-1/2	
Prewired 230V	230V	
Model Number	JTM-1055	
Brand	Jet	
Overall Dimensions	108 X 80 X 92	
Height	92	inch
Width	80	inch
Length	108	inch
Net Weight	3300	pound



Email: sales@scottmachinery.com

Phone# 916-638-7718

Website: www.scottmachinery.com