



Providing Solutions.

Phone: 916-638-7718 Fax: 916-638-2450

www.scottmachinery.com

4700 Lang Ave, Suite D, McClellan, CA 95652

- ◆ Dual mitering 45° L and 60° R
- ◆ Inverter driven
- ◆ 1-1/4" Blade
- ◆ Digital readout for blade speed
- ◆ Blade brush with chip collection drawer
- ◆ Quick lock vise
- ◆ Automatic descent and raise of the bow head
- ◆ 220V 3-phase

Band Saws – BS-20SA-DM

SPECIFICATIONS – BS-20SA-DM

SPECIFICATIONS – BS-20SA-DM		
Capacity		
Round (90°/45°/60°)	13" / 12" / 8.5"	330 mm / 305 mm / 215 mm
Square (90°/45°/60°)	13" / 12" / 8.5"	330 mm / 305 mm / 215 mm
Rectangular (90°)	13" x 18" / 13" x 10.6" / 12.4" x 7.7"	330 x 460 mm / 330 x 270 mm / 315 x 195 mm
Blade Size (H x W x L)	1.25" / .042" / 162.6"	34 mm / 1.1 mm / 4130 mm
Blade Speed (fpm)	60 – 306 Inverter Driven	
Blade Guide	Carbide / Roller	
Miter Angle	0 – 60°	
Miter Adjustment	Dual Miter Swivel Head	
Descent Control	Pressure Assist Hydraulic	
Return	Hydraulic	
Drive	Inverter Direct	
Motor	3 hp	
Power	220V / 3-Phase	
Shipping Dimensions (L x W x H)	88.6" x 35.5" x 61.4"	2250 x 902 x 1560 mm
Shipping Weight	2,156 lbs.	980 kgs.

Specifications subject to change without notice.



SCAN FOR MORE INFORMATION