

R-H55

Roll Bender
Hydraulic

SPECIFICATIONS

Capacity	Size	Min Diameter
Pipe	2.5" (Sch. 40)	40"
Round Tube	4" (.083")	72"
Square Tube	2.75" (.083")	54"
Angle Iron	3" (.250")	36"
Solid Square	1.75"	28"
Solid Round	2"	28"
Flat Bar		
Easy Way	5" (.75")	28"
Hard Way	3.5" (.675")	32"
Roll Adjustment	Hydraulic	
Pinch	Single	
Shaft Diameter	2.165"	
Roll Diameter		
Upper	6.693"	
Lower	6.693"	
Shaft Center Distance (Lower Rolls)	11.875"	
Driven Rolls	3	
Digital Readout	Yes	
Speeds	11 rpm	
Motor	5 HP	
Power Requirement	220V / 3-phase	
Shipping Dimensions (L / W / H)	60" / 44" / 68"	
Shipping Weight	1728 Lbs	

Specifications subject to change without notice.



Digital readout



SCOTT

MACHINERY

Ph. (916) 638-7718
Fx. (916) 638-2450
Email: sales@scottmachinery.com
4700 Lang Avenue, Suite D
McClellan, CA 95652

Three driven rolls
Hydraulic top roll positioning
Bends vertically or horizontally
Digital readout
220V, 3-phase

