



ELITE110

Superior 4 Station Ironworker

Universal Open Tooling Station
ANSI B11.5-1988R(02) Compliant
ETL/UL Approved Controls

ELITE Integrated Features:

Hydraulic Hold-Down
E-Stop / Lockout-Tagout
Electric Stroke Control
Hydraulic Accessory Pack
Central Lubrication System

Swing-Away Stripper Assembly
Roller Encoder Measuring System
Quick Change Punch Assembly
Premium Gauging Tables
LED Lighting



Shown with
optional Coper Notcher

PUNCH

Rating: 110 Tons
Max. Capacity: 1-3/8" Dia. in 1" A36
Stroke: 1-13/16"
Throat Depth: 11-3/4"
Open Height: 8-5/8"
Shut Height: 6-13/16"
Work Height: 41"

FLAT BAR SHEAR

Max. Capacity: 3/4" x 14"
1" x 12"
Max. Round: 1-1/4"
Max. Square: 1-1/4"
Work Height: 41-1/2"

ANGLE SHEAR

Max. Capacity: 6" x 6" x 1/2"
Work Height: 50-7/8"

OPEN STATION

Throat Depth: 15-1/2"
Open Height: 8-5/8"
Shut Height: 6-13/16"
Stroke: 1-13/16"
Work Height: 39-3/16"

OPTIONAL COPER NOTCHER

Max. Capacity: 2-1/2" x 6" x 1/2"
Work Height: 44-3/16"

GENERAL SPECIFICATIONS

Standard Motor:	7.5 HP 3~ 208 V or 230 V 1765 RPM 22 A
Optional Motors:	7.5 HP 3~ 460 V 1765 RPM 11 A 7.5 HP 3~ 575 V 1770 RPM 8 A 7.5 HP 1~ 208 V or 230 V 1765 RPM 36 A
Hydraulic Pump:	10-1/2 GPM - 2 Stage
Valve Pressure:	3000 PSI
Reservoir:	17 Gallons
Cylinder:	3-1/2" Ram

DIMENSIONS

Height:	66-1/16"
Width:	57-1/4"
Depth:	42-3/8"
Shipping Weight:	5380 lb



Providing Solutions.

Phone: 916-638-7718 Fax: 916-638-2450

www.scottmachinery.com

4700 Lang Ave, Suite D, Mcclellan, CA 95652