



Providing Solutions.

Phone: 916-638-7718 Fax: 916-638-2450

www.scottmachinery.com

4700 Lang Ave, Suite D, McClellan, CA 95652

W.F. WELLS MODEL F-16-2

Specifications

Capacity.....	Rectangular at 90° 16" High x 20" Wide, Round at 90° 16" Diameter	
	Rectangular at 45° 16" High X 9" Wide, Round at 45° 9" Diameter	
Weight Capacity.....	5,000 lbs	
Blade Speed	60-425 SFPM	
Blade Size	1¼" X .042" X 15'	
Blade Guide.....	Rollers and Carbide Side Blocks	
Blade Tension.....	Hydraulic	
Bandwheel Size	20"	
Vise	Full Stroke Hydraulic, 8-1/2"	Voltage 208-60-3
Blade Drive	7½ HP, AC Vector Drive	230-60-3
Sawing Force.....	0-750 lbs	460-60-3
Coolant Capacity	15 Gallons	575-60-3 (5 HP)
Hydraulic Capacity	20 Gallons	
Hydraulic Drive	2 HP Motor	
Work Height.....	26"	
Shipping Weight.....	2,450 lbs	
Electrics	Wired to NFPA 79 Machine Tool Standards	
Machine Dimensions.....	97" Length x 49" Width x 83" Height	

OPTIONAL FACTORY INSTALLED ACCESSORIES

Description

- Automatic Length Stop Assembly
- Discharge Worktable, 20" W x 48" L with Stock Stop
- Work Light, Wired In
- Blade Break/Stall Switch
- Hydraulic Chip Conveyor
- Hydraulic Holddown, Saw Vise
- Hydraulic Swivel Base with Miter Vise (See M-16-2)
- Hydraulic Powered Conveyor 21" X 10'
- High Speed Drive & Guides (1" Blade) 400-3000 SFPM
- Hour Meter
- Free Standing Roller Stock Conveyors, 6" Centers:
 - 18" X 5' X 2,500 lbs Cap. Distributed Weight
 - 18" X 10' X 5,000 lbs Cap. Distributed Weight
 - 21" X 5' X 5,000 lbs Cap. Distributed Weight
 - 21" X 10' X 10,000 lbs Cap. Distributed Weight

Consult Factory For Additional Accessories

*Prices and specifications subject to change without notice

