

24 JUNIOR

By far the most popular of all Pittsburgh machines. Ideal for jobsite manufacturing, smaller or startup companies. The 24 Junior will form the 5/16" Pittsburgh Lock on 24 Ga. and lighter galvanized metal. Manufactured with top mount starter and a convenient cabinet overhang, this unit can be bench mounted. Or it can be freestanding if purchased with the optional floor stand. Add the optional flanging attachment to produce all of your fitting needs.

SPECIFICATIONS

- Capacity: 24 Ga.
- Speed: 30 fpm
- Depth of Pocket: 5/16" - uses approximately 1" of material
- Motor: 1/2 HP 115/1/60/1800 RPM
- Dimensions: 32" long, 16" wide, 14" high
- Shipping Weight: 150 lbs.

Shown with optional Flanging Attachment and Floor Stand



22 PORTABLE

Originally designed by Roy Flagler in 1949, the 22 Portable Pittsburgh will form the 5/16" Pittsburgh Lock on 22 Ga. and lighter galvanized metal. This machine also has extended shafts for auxiliary tooling. The 22 Portable is manufactured with top mount starter and a convenient cabinet overhang, this unit can be bench mounted. Or it can be freestanding if purchased with the optional floor stand. Add the optional flanging attachment to produce all of your fitting needs.

SPECIFICATIONS

- Capacity: 22 Ga.
- Speed: 17 fpm
- Depth of Pocket: 5/16" - uses approximately 1" of material
- Extended Shafts: For 1 set of Auxiliary Tooling
- Motor: 1/2 HP 115/1/60/1800 RPM
- Dimensions: 34" long, 16" wide, 14" high
- Shipping Weight: 200 lbs.

AUXILIARY TOOLING AVAILABLE

(All are 22 Ga. Capacity unless noted)

- 3/8" Double Seam Rolls
- 1 1/8" Drive Cleat Rolls
- 3/8" Right Angle Flange Rolls
- 1/4" x 180 Degree Closed Hem Rolls (26 Ga.)

Shown with optional Flanging Attachment and Floor Stand

